


API 5CT, 5L ГОСТ 632, 633, 8732		ДИАПАЗОН ПРОДУКЦИИ ТОО "KSP Steel"																																					
НАРУЖНЫЙ ДИАМЕТР OUTER DIAMETER		ТОЛЩИНА СТЕНКИ WALL THICKNESS																																					
В дюймах inches	В мм. mm.	3,4	3,7	3,9	4,1	4,9	5,0	5,2	5,3	5,4	5,5	5,6	5,7	6,0	6,4	6,6	7,3	8,6	9,0	9,2	9,3	9,5	10,0	10,5	12,0	13,8	14,5	15,9	18,3	20,0	22,2	23,0	25,4	27,1	27,2	28,8	31,8	35,0	40,0
2.3/8"	60,3	<p>Трубы насосно-компрессорные с высаженными (или невысаженными) концами, обсадные и нефтепроводные</p> <p>Pipes: tubing pipes with upset (non-upset) ends, casing and line pipes</p>																																					
2.7/8"	73,0																																						
3.1/2"	88,9																																						
4.1/2"	114,3																																						
5"	127,0																																						
5.1/2"	139,7	<p>Трубы обсадные, нефтепроводные</p> <p>Casing and line pipes</p>																																					
5.9/16"	141,3																																						
5.3/4"	146,1																																						
-	159,0																																						
6.5/8"	168,3																																						
7"	177,8																																						
7.5/8"	193,7																																						
8.5/8"	219,1																																						
9.5/8"	244,5																																						
9.7/8"	250,8																																						
10.3/4"	273,1																																						
11.3/4"	298,5																																						
12.3/4"	323,9																																						
13.3/8"	339,7																																						
13.5/8"	346,1																																						